

---

**PROJECT:**

---

**SCHEDULE:** **DATE:**

---

**PREPARE BY:**

---

**NOTES:**

---

**FLUSH MOUNT COMPACT (FMC)**

**DESCRIPTION**

naturalLED<sup>®</sup> Compact Flush Mounts (FMC) are an excellent replacement solution for traditional flush incandescent and florescent ceiling and wall mounted fixtures. Perfect for smaller or limited spaced areas with a contemporary design to replace 75W to 120W incandescent fixtures. Our FMC series is easy to install and can be mounted to a 4-inch junction box. The FMC is dimmable, wet rated and equipped with the latest DOB (Driver on Board) technology, which increases the performance reliability over its lifetime. Perfect for residential, commercial and hospitality applications. Ideal for bathrooms, closets, small rooms, storage areas, hallways and stairways.



**FEATURES**


- Wet/Damp Location
- Voltage: 120V
- Powerfactor >0.9
- Dimmable
- Operating temperature: -4°F - 113°F
- Uniform light distribution and consistent color
- Easy installation
- UV coated acrylic
- Retrofit for Incandescent and CFL Flush Mount
- Color: White

**INCLUDED WITH FIXTURE**

E26 Base for  
17-Watt FMC



J-Box Bracket for  
17-Watt FMC



**APPLICATIONS**

- Bathroom Lighting
- Decoration Lighting
- Hallway Lighting
- Bedroom Lighting
- Hospitality Lighting
- Shower Room Lighting

**WARRANTY**


- 5 Year Warranty

Ordering Information		EXAMPLE: LED7FMC-70L830			
LED	7	FMC	70L	8	30
LED	Size	Series	Lumens	CRI	Color Temp
	7	FMC	70L	8 CRI80	30 3000K
	7-inch Diameter	Flush Mount Compact	700 Lumens		

ORDERING

Watts (W)	Ordering Code	Description	Color Temp (K)	Lumens (lm)	Voltage	Equiv. Wattage (W)	Rated Hrs	Damp/Wet Location
10	7454	LED7FMC-70L830	3000K	700	120V	75	50,000	D
10	7455	LED7FMC-70L840	4000K	700	120V	75	50,000	D
10	7456	LED7FMC-70L850	5000K	700	120V	75	50,000	D
17	7056	LED7FMC-110L840	4000K	1,150	120V	120	50,000	W
17	7057	LED7FMC-110L850	5000K	1,180	120V	120	50,000	W


SPECIFICATIONS



Wattage	Diameter ( D )	Height ( H )	Weight ( lbs )
10W	7" (178mm)	1.75" (44.5mm)	1.02
17W	7.25" (184mm)	1.25" (32mm)	1.00

PHOTOMETRICS CHART


10 Watt (700 Lumens)



Illuminance at a Distance			
Center Beam f.c.	Beam Width		
1.7ft	97.0 fc	3.9 ft	3.9 ft
3.3ft	25.7 fc	7.6 ft	7.5 ft
5.0ft	11.2 fc	11.5 ft	11.4 ft
6.7ft	6.24 fc	15.4 ft	15.3 ft
8.3ft	4.07 fc	19.1 ft	18.9 ft
10.0ft	2.80 fc	23.0 ft	22.8 ft

■ Vert. Spread: 97.9°  
■ Horiz. Spread: 97.4°

17 Watt (1,100+ Lumens)



Illuminance at a Distance			
Center Beam f.c.	Beam Width		
1.7ft	141 fc	5.2 ft	5.2 ft
3.3ft	37.4 fc	10.1 ft	10.0 ft
5.0ft	16.3 fc	15.3 ft	15.2 ft
6.7ft	9.07 fc	20.5 ft	20.4 ft
8.3ft	5.91 fc	25.4 ft	25.2 ft
10.0ft	4.07 fc	30.6 ft	30.4 ft

■ Vert. Spread: 113.6°  
■ Horiz. Spread: 113.3°

PACKAGE

Master Pack: 10 pcs

