

**PAR PAR LAMPS & OUTDOOR RATED**

PROJECT: \_\_\_\_\_

SCHEDULE: \_\_\_\_\_ DATE: \_\_\_\_\_

PREPARE BY: \_\_\_\_\_

NOTES: \_\_\_\_\_

**DESCRIPTION**

naturaLED® PAR LED bulb provides a superior replacement for all incandescent PAR lamp applications. An energy efficient integrated LED driver deliver the same lumen output equivalent with up to 78% energy savings. Our PAR lamps are direct replacement with energy star certification for wet or damp locations. Perfect for display case lighting, track lighting, jewelry lighting and general lighting.



**APPLICATIONS**

Display Case, Recessed, Accent, General, Residential, Restaurant



**Rated Life Hours 25,000**  
**Warranty 5 Years**

**FEATURES**

- Damp Location
- Wet Location (outdoor rated)
- UL Listed
- ColorTemp: 3000K, 4000K, 5000K
- Voltage: 120V
- Power Factor: >0.9
- Beam Angle: 40°
- Dimmable
- CRI: >90
- Operating temperature: - 4°F - 104°F
- Instant on / Uniform light distribution and consistent color
- Up to 78% energy savings
- Direct Replacement traditional incandescent design
- Contains no mercury or lead
- Year Warranty
- 25,000 hrs rated average life

**SAMPLE NUMBER LED8PAR20/50L/FL/930**

STYLE	WATTAGE	SERIES	SHAPE	LUMENS	BEAM ANGLE	CRI/COLOR TEMP
LED	8	PAR	20	50L	FL	930
LED Lighting	8 Watt	PAR Lamp	PAR 20	500 Lumens	Flood	CRI 90 3000K



# PAR20,30,30L,38

LAMPS


## ORDERING

W=Wet Location / D=Damp Location


Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Base	CRI	Equiv. Wattage (W)	Damp/Wet Location
8	<b>5924</b>	LED8PAR20/50L/FL/930	3000K	500	E26	90	50	D
8	<b>5925</b>	LED8PAR20/50L/FL/950	5000K	500	E26	90	50	D
10	<b>5926</b>	LED10PAR30/80L/FL/930	3000K	800	E26	90	75	D
10.5	<b>5927</b>	LED10PAR30/80L/FL/950	5000K	800	E26	90	75	D
10.5	<b>5928</b>	LED10PAR30L/OD/80L/FL/930	3000K	800	E26	90	75	W
10.5	<b>5997</b>	LED10PAR30L/OD/80L/FL/940	4000K	800	E26	90	75	W
10.5	<b>5929</b>	LED10PAR30L/OD/80L/FL/950	5000K	800	E26	90	75	W
15	<b>5930</b>	LED15PAR38/OD/120L/FL930	3000K	1,200	E26	90	100	W
15	<b>5998</b>	LED15PAR38/OD/120L/FL940	4000K	1,200	E26	90	100	W
15	<b>5931</b>	LED15PAR38/OD/120L/FL950	5000K	1,200	E26	90	100	W

## DIMENSIONS


**PAR20**  
3.68-oz




**PAR30**  
6.56-oz



**PAR30L**  
7.68-oz




**PAR38**  
12.64-oz



## PACKAGE

**Case Qty PAR20/30**  
20 pcs (10 for inner package)



**Case Qty PAR38**  
10 pcs

