

Version	2.0	Date	1/26/25
Prepared By	JC		

PRODUCT SPECIFICATION			
Category	Slim Area Light		
Item Number	9715		
Stock Code	SAL75S/T3/8C3/BK-Z10		
Mounting	Pole Mount/ Slip Fitter/ Yoke Mount/ Wall Mount		
Housing Color	Black		



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	25/42/50/75	Replacement Wattage (W)	100-400
Tested Wattage (W)	-		
Input Voltage (V)	120-277		
Voltage Frequency (Hz)	50/60	Surge Protect Level	10KV
Input Current (A)	0.68	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%	Z10 Receptacle	Yes

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	3,500 5,800 7,000 10,500	CCT (K)	CCT3 (30/40/50K)
Efficacy (lm/w)	140	Beam Angle (°)	Type 3
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 140°F
IP Rating	IP66
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	7

ACCESSORIES		
Item #	Stock Code	Description
P10520	SEN-ANT-5-Z10-PC	Photocell
P10522	SEN-ANT-6-Z10	Motion Sensor
P10316	SEN-BRI-RC100	Remote Controller
P10488	CTL-MW-PSC-ZKV-WCM-100-BLE-SR	Bluetooth controller, 0-10V, 12-24Vdc, Z10 Brown ☐
P10517	CTL-MW-PSC-ZKV-WCM-110-BLE-SR-BN	Bluetooth controller w/ Photocell, 0-10V, 12-24Vdc, Z10 Brown☐

*See Page 2 for more accessories

PRODUCT DIMENSIONS		
Width- in / (mm)	12.01"307	Front view showing two light modules with a width of 12.01 in (307mm) and a height of 14.2 in (360mm). The side view shows a depth of 2.6 in (66mm). The rear view shows mounting brackets and a cable length of 1.64 ft.
Height- in / (mm)	2.60"66	
Depth- in / (mm)	14.20"360	
EPA (ft²)	0.212 ft² (@ 0 deg)	
Weight (lbs)	8	
Mounting Height (ft)	10~25	
Cable Length (ft)	1.64	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS

Version	2.1	Date	1/26/25
Prepared By	JC		

ACCESSORIES		
Item #	Stock Code	Description
P10523	MT-AL/PMA8/BZ	Mount - Area Light Adjustable Pole Mount 8" Bronze
P10525	MT-AL/PMA8/BK	Mount - Area Light Adjustable Pole Mount 8" Black
P10524	MT-AL/PMA8/WH	Mount - Area Light Adjustable Pole Mount 8" White
P10453	MT-AL/PM6/BZ	Mount - Area Light Pole Mount 6" Bronze
P10468	MT-AL/PM6/BK	Mount - Area Light Pole Mount 6" Black
P10458	MT-AL/PM6/WH	Mount - Area Light Pole Mount 6" White
P10455	MT-AL/SF/BZ	Mount - Area Light Slip Fitter Bronze
P10470	MT-AL/SF/BK	Mount - Area Light Slip Fitter Black
P10460	MT-AL/SF/WH	Mount - Area Light Slip Fitter White
P10473	MT-AL/WM/BZ	Mount - Slim Area Light Wall Mount Bronze
P10475	MT-AL/WM/BK	Mount - Slim Area Light Wall Mount Black
P10474	MT-AL/WM/WH	Mount - Slim Area Light Wall Mount White
P10456	MT-SAL/YK12/BZ	Mount - SAL Yoke Mount 12" Bronze
P10471	MT-SAL/YK12/BK	Mount - SAL Yoke Mount 12" Black
P10461	MT-SAL/YK12/WH	Mount - SAL Yoke Mount 12" White
P10481	GSFB-SAL/BZ	Glare Shield - SAL Bronze 150W (340W requires 2 per fixture)
P10483	GSFB-SAL/BK	Glare Shield - SAL Black 150W (340W requires 2 per fixture)
P10482	GSFB-SAL/WH	Glare Shield - SAL White 150W (340W requires 2 per fixture)
P10467	LENS-SAL-T4-G1	Type 4 Lens for SAL 150W requires 2 per fixture (340W requires 4 per fixture)
P10499	LENS-SAL-T5-G1	Type 5 Lens for SAL 150W requires 2 per fixture (340W requires 4 per fixture)
P10500	LENS-SAL-T3-BLC-G1	Type 3 Back Light Cut Lens for SAL 150W requires 2 per fixture (340W requires 4 per fixture)