

Version	2.1	Date	1/26/25
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Slim Area Light
Item Number	9721
Stock Code	SAL150S/T3/8C3/BK/480-Z10
Mounting	Pole Mount/ Slip Fitter/ Yoke Mount/ Wall Mount
Housing Color	Black



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	90 / 120 / 150	Replacement Wattage (W)	400-575
Tested Wattage (W)	-		
Input Voltage (V)	277-480V	Surge Protect Level	20KV
Voltage Frequency (Hz)	50/60		
Input Current (A)	1.36	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%	Z10 Receptacle	Yes

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	12,600	CCT (K)	CCT3 (30/40/50K)
	16,800		
	21,000		
Efficacy (lm/w)	140	Beam Angle (°)	Type 3
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 140°F
IP Rating	IP66
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	7

ACCESSORIES		
Item #	Stock Code	Description
P10520	SEN-ANT-5-Z10-PC	Photocell
P10522	SEN-ANT-6-Z10	Motion Sensor
P10316	SEN-BRI-RC100	Remote Controller
P10488	CTL-MW-PSC-ZKV-WCM-100-BLE-SR	Bluetooth controller, 0-10V, 12-24Vdc, Z10 Brown ☑
P10517	CTL-MW-PSC-ZKV-WCM-110-BLE-SR-BN	Bluetooth controller w/ Photocell, 0-10V, 12-24Vdc, Z10 Brown☑

\*See Page 2 for more accessories

PRODUCT DIMENSIONS		
Width- in / (mm)	12.01" / 307	
Height- in / (mm)	2.60" / 66	
Depth- in / (mm)	14.20" / 360	
EPA (ft²)	0.212 ft² (@ 0 deg)	
Weight (lbs)	8	
Mounting Height (ft)	10~25	
Cable Length (ft)	1.64	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS